



# THERMA - TITE™ | 3000

Therma-Tite™ 3000 is a two component, 2.9lb density, one to one by volume spray foam designed for roofing systems. Therma-Tite™ 3000 is intentionally formulated without harmful HFCs, leading to an exceptionally low Global Warming Potential (GWP.) This system creates continuous insulation without any thermal breaks, ensuring exceptional resistance to wind uplift. It also boasts self-flashing properties, guaranteeing a watertight and durable roofing system.

## DEFINING EXCELLENCE THROUGH INNOVATION

### ENERGY EFFICIENT

With a higher R-Value per inch compared to traditional roofing insulations, SPF systems significantly enhance building efficiency, leading to reduced energy costs and a more sustainable structure.

### LIGHTWEIGHT ADVANTAGE

Adding minimal weight to the building structure, SPF systems are particularly favored for remedial roofing applications, ensuring structural integrity without imposing unnecessary burdens.

### PROVEN TECHNOLOGY

Spray foam was developed in the late 1930's and was used commercially in the 1940's with exponential growth thereafter.

### SEAMLESS INTEGRATION

The fully adhered application of SPF roofing requires no fasteners, ensuring a seamless and monolithic structure that eliminates thermal bridging, contributing to a more efficient and resilient roofing system.

## Contact Us



(812) 776-6727

[sprayips.com](http://sprayips.com)

4117 Capital Drive, New Albany, IN 47150

**IPS**  
INNOVATIVE  
POLYMER SYSTEMS

